







Aqueous well treatment fluid containing hydrophobically modified cellulose derivatives as fluid loss reducer and method of use.

Patent number: EP0670359
Publication date: 1995-09-06
Inventor: AUDIBERT ANNIE (FR); ARGILLIER JEAN-FRANCOIS (FR); BAILEY LOUISE (GB); REID PAUL I (GB)
Applicant: INST FRANCAIS DU PETROL (FR); SOFITECH NV (BE)
Classification:
- international: **C09K8/10; C09K8/20; C09K8/514; C09K8/588; C09K8/90; C09K8/02; C09K8/50; C09K8/58; C09K8/60; (IPC1-7): C09K7/02; E21B43/22; E21B43/25**
- european: **C09K8/10; C09K8/20C; C09K8/514; C09K8/588; C09K8/60D4B8**
Application number: EP19950400397 19950224
Priority number(s): FR19940002572 19940303

Also published as:

 FR2716928 (A1)
 EP0670359 (B1)
 NO316321B (B1)

Cited documents:

 US4529523
 EP0314118
 SU979483

Report a data error here

Abstract of EP0670359

A procedure used in well drilling across at least one geological formation having a given permeability in which one of the following operations is effected : well drilling conditioning and intervention. The permeability of the walls of the drilled well in the formation is controlled by the addn. of a determin. amt. of at least one cellulosic deriv. modified hydrophobically in a vol. of water-based fluid, placed in the well during operation. Also claimed is the fluid compsn. used in the process.

Data supplied from the **esp@cenet** database - Worldwide